



RED LINE 60WT DRAG RACE OIL (20W60)



- Popular in Top Alcohol and Pro Mod classes, AHDRA Nitro bikes and blown alcohol Tractor Pulling
- Can be heated to evaporate fuel dilution and re-use
- Improved valvetrain wear, less piston scuffing and improved bearing wear

TYPICAL PROPERTIES:

SAE Viscosity Grade	20W60
Vis @ 100°C, cSt	25
Vis @ 40°C, cSt	197
Viscosity Index	158
CCS Viscosity, Poise, @ °C	30@-10°C
Pour Point, °C	-40
Pour Point, °F	-40
Zinc, avg PPM	2250
Phosphorus, avg PPM	2000
NOACK Evaporation Loss, 1hr @ 482°F (250°C), %	6

PACKAGE SIZES:

- 10604 - 60WT Drag Race Oil (20W60) - quart
- 10605 - 60WT Drag Race Oil (20W60) - 1 gallon
- 10606 - 60WT Drag Race Oil (20W60) - 5 gallon
- 10608 - 60WT Drag Race Oil (20W60) - 55 gallon

ABOUT RED LINE MOTOR OIL FOR RACING

- Reformulated for improved frictional properties
- Special detergents for improved lubricity and less detonation
- Polyol ester base stocks provide more stability and film strength when exposed to excess fuel dilution
- Each of these products has no less than 2200ppm of zinc and phosphorus for antiwear
- Each race oil product is a multi-grade, offering 2-4% more power than oil of a similar viscosity - 20WT is a 5W20, 30WT is a 10W30, 40WT is a 15W40 and 50WT is a 15W50
- Improved protection at startup, lower oil temp and cleanliness
- Remember to change these oils more frequently than regular motor oils

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM