



RED LINE 20W60 MOTORCYCLE OIL



- Recommended for V-twins that need more viscosity due to operation in extremely hot climates.
- Popular for Evos and Twin Cam engines with big bore kits, stroker kits or issues with valvetrain noise
- Specifically blended for air-cooled V-Twin engines with traditionally wide clearances like Knucklehead, Shovelhead and Panhead engines.
- Superior film strength through the use of ester base stocks for protection and ring seal
- Extended drain intervals over other brands due to higher quality base stocks and excellent dispersants

TYPICAL PROPERTIES:

API Service Class	JASO MA SJ/SG/SH
SAE Viscosity Grade (Motor Oil)	20W60
Vis @ 100°C, cSt	23
Vis @ 40°C, cSt	177
Viscosity Index	161
CCS Viscosity, Poise, @ °C	90@ -15
Pour Point, °C	-45
Pour Point, °F	-49
Zinc, avg PPM	2125
Phosphorus, avg PPM	2100
Molybdenum, avg PPM	425
NOACK Evaporation Loss, 1hr @ 482°F (250°C), %	5
% Viscosity Loss, 30 Pass ASTM D6278	0
HTHS Vis, cP @150°C, ASTM D4741	7.0

RECOMMENDED FOR:

JASO MA
API SJ/SG/SH

PACKAGE SIZES:

12604 - 20W60 Motorcycle Oil - quart
12606 - 20W60 Motorcycle Oil - 5 gallon
12608 - 20W60 Motorcycle Oil - 55 gallon

ABOUT RED LINE MOTORCYCLES, ATVS AND POWERSPORTS

- Motor oils and gear oils are specifically engineered for the latest high-revving four-stroke motocross bikes, ATVs, Sportbikes and V-Twins
- Each gear oil product reduces the thinning effect from high temperatures
- Motor oils are packed with higher levels of anti-wear chemistry like zinc and phosphorus
- Special friction modifiers in our motor oils better wet-clutch operation
- A variety of Two-Stroke oils to meet the NMMA TC-W3 regulations where required

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM