



RED LINE 50WT DRAG RACE OIL (15W50)



- Used in applications with wider bearing clearances
- Popular with sprint and midget applications on methanol -- offers less frequent oil changes due to less fuel dilution

TYPICAL PROPERTIES:

SAE Viscosity Grade	15W50
Vis @ 100°C, cSt	19.2
Vis @ 40°C, cSt	135
Viscosity Index	141
CCS Viscosity, Poise, @ °C	35@-15°C
Pour Point, °C	-45
Pour Point, °F	-49
Zinc, avg PPM	2350
Phosphorus, avg PPM	2050
NOACK Evaporation Loss, 1hr @ 482°F (250°C), %	6

PACKAGE SIZES:

- 10504 - 50WT Race Oil (15W50) - quart
- 10505 - 50WT Race Oil (15W50) - 1 gallon
- 10506 - 50WT Race Oil (15W50) - 5 gallon
- 10508 - 50WT Race Oil (15W50) - 55 gallon

ABOUT RED LINE MOTOR OIL FOR RACING

- Reformulated for improved frictional properties
- Special detergents for improved lubricity and less detonation
- Polyol ester base stocks provide more stability and film strength when exposed to excess fuel dilution
- Each of these products has no less than 2200ppm of zinc and phosphorus for antiwear
- Each race oil product is a multi-grade, offering 2-4% more power than oil of a similar viscosity - 20WT is a 5W20, 30WT is a 10W30, 40WT is a 15W40 and 50WT is a 15W50
- Improved protection at startup, lower oil temp and cleanliness
- Remember to change these oils more frequently than regular motor oils

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM